

AVC8000nano

8x D1 Video Frame Grabber for mini PCI Express



**Advanced Micro
Peripherals**

THE EMBEDDED VIDEO EXPERTS

The AVC8000nano is a high-performance 8-channel video capture and overlay controller on a single Mini PCI Express card. The AVC8000nano provides a powerful and flexible solution for capturing up to eight concurrent analog video inputs for local system display or software analysis and processing, ideal for embedded Situational Awareness systems in the most demanding environment.



The AVC8000nano allows each of the 8 video channels to be captured at full D1 size, all at full frame rate. The captured video data can be streamed continuously to system memory or disk for either immediate local display or further processing. The capture engine of the AVC8000nano features hardware color space conversion to present the captured video data in the format best suited to the end application.

The AVC8000nano is supported by drivers for Windows and Linux.

Rev A.02

Subject to change without notification

Advanced Micro Peripherals Ltd
Cambridge, CB6 2HY, England
Tel (+44) 1353 659500
Fax (+44) 1353 659600
sales@ampitd.com
<http://www.ampitd.com>

Advanced Micro Peripherals Inc
New York, NY10016, USA
Tel (+1) 212 951 7205
Fax (+1) 212 951 7206
sales@amp-usa.com
<http://www.amp-usa.com>

Live Frame Capture
up to 8 full size D1
PAL/NTSC/RS170
video inputs at full
frame rate.



AVC8000nano

8x D1 Video Frame Grabber for mini PC1 Express



Applications

High performance image capture

Vehicle-based Video Capture

Real-time Situational Awareness

Law Enforcement

Crime Scene Recording

Remote Video Surveillance

Multi-camera Security Application

Asset Monitoring

Traffic Monitoring and Control

Video Acquisition and Analytics

Multi-Camera video
preview to system

VGA

Very Low Latency

Advanced Micro Peripherals Ltd
Cambridge, CB6 2HY, England
Tel (+44) 1353 659500
Fax (+44) 1353 659600
sales@ampitd.com
<http://www.ampitd.com>

Advanced Micro Peripherals Inc
New York, NY10016, USA
Tel (+1) 212 951 7205
Fax (+1) 212 951 7206
sales@amp-usa.com
<http://www.amp-usa.com>




AVC8000nano

8x D1 Video Frame Grabber for mini PCI Express



**Advanced Micro
Peripherals**

THE EMBEDDED VIDEO EXPERTS



AVC8000nano Functional Diagram

Windows

DirectShow

and

Linux V4L

support

Features

- 8 Live NTSC/PAL video inputs
- 8 x D1 size capture at full frame rate
- Windows DirectShow/DirectDraw support
- Efficient PCI DMA cycle operation
- Linux Video4Linux support
- Drivers for Windows, Linux
- Robust PC/104-Express construction
- Low Power Operation

Advanced Micro Peripherals Ltd
Cambridge, CB6 2HY, England
Tel (+44) 1353 659500
Fax (+44) 1353 659600
sales@amp ltd.com
<http://www.amp ltd.com>

Advanced Micro Peripherals Inc
New York, NY10016, USA
Tel (+1) 212 951 7205
Fax (+1) 212 951 7206
sales@amp-usa.com
<http://www.amp-usa.com>



Mini PCI Express Bus Interface

Full height Mini PCI Express card
Live video capture to display, memory or disk

Analog Video Input

Up to 8 concurrent composite PAL or NTSC video input channels
Eight 10-bit Analog-to-Digital converters
Anti-aliasing filters on inputs

Video Input Formats

NTSC-M, NTSC-Japan, NTSC (4.43), RS-170
PAL-B,G,N, PAL-D, PAL-H, PAL-I, PAL-M, PAL-CN, PAL-60
SECAM

Video Input Adjustments

Contrast (or luma gain) adjustable from 0 - 255% of original
Saturation (or chroma gain) adjustable from 0 - 200% of original
Hue (or chroma phase) adjustable from -36° to +36°
Brightness (or luma level) can be adjusted from -128 to 127 steps
Software adjustable Sharpness, Gamma and noise suppression

Video Capture Formats

RGB555, RGB565
YCbCr 4:2:2
YCbCr 4:1:1

System Requirements

x86 PC-Compatible with mini PCI Express socket
PCI VGA Display (if Video Preview to host is required)

Miscellaneous

Operating temp 0°C to 60°C
Operating temp -40°C to +85°C (extended temp option)
Standard Full Height Mini PCI Express form factor

Software Drivers

Drivers for Windows, Linux
Sample video overlay and capture application in C/C++ source code

Ordering Information

AVC8000nano	Video Capture and Overlay Controller (0 to 60°C)
AVC8000nano-EXT	Video Capture and Overlay Controller (-40°C to +85°C)

**AVC8000nano**