

AVA-5520

Rugged, Fanless AIoT Platform with NVIDIA Quadro® GPU Embedded for Real-time Video/Graphics Analytics

Features

- 6th/7th Gen Intel® Core™ i7 Processors, up to 32GB
- NVIDIA Quadro® GPU MXM 3.1 Type A/B module on PCI Express x16
- 8x M12 GbE (4x PoE), 4x RS-422, 4x USB 3.0, 1x DVI-I, 4x DisplayPort with lockable connectors
- Multiple storage options: 2x 2.5" SATA 6.0 Gb/s drive bays, 1x M.2 2280 slot, 1x CFast socket
- GNSS/3G/4G/WLAN support via 2x Mini PCIe slots and 2x USIM slots
- 4x isolated DI and 4x isolated DO
- +12VDC power input



Specifications

System

Processor

6th/7th Gen Intel® Core™ i7 processors (formerly Skylake and Kaby Lake)
 Intel® Core™ i7-6820EQ CPU, 2.8GHz
 Intel® Core™ i7-7820EQ CPU, 3.0GHz

Memory

Dual channel DDR4-2133 SDRAM with dual SODIMM sockets, up to 32GB

BIOS

AMI UEFI

Storage

2x 2.5" SATA drive bays
 1x CFast slot, externally accessible
 1x M.2 2280 (SATA)

Graphics

2x DisplayPort from Intel processor
 4x DisplayPort with lockable design from GPU MXM (SKU dependent)
 1x DVI-I from Intel processor

Connectivity

Ethernet

2x RJ-45 1000BASE-T Ethernet ports
 4x M12 X-coded 1000BASE-T Ethernet ports with PoE Class 2 (7W), 1.5kV isolation
 4x M12 A-coded 1000BASE-T Ethernet ports, 1.5kV isolation

USB

4x USB 3.0 Type A ports

Serial Port

4x DB-9 RS-232/422/485 ports (RS-422 by default)
 2kVrms isolation

Digital I/O (optional)

4x isolated DI and 4x isolated DO via two DB-9 connectors, supported by add-on module (occupies one 2.5" drive space)

DI: 0-24V input voltage with 1500VDC isolation

DO: 3.3V-35VDC output voltage, 250mA/ch sink current, 1500VDC isolation

Audio

Mic-in/ Line-out ports

Wireless

2x Mini PCIe card slots are available for cellular modem or WLAN modules

Compliant to Mini PCIe card spec v1.2 (PCIe and USB 2.0)

Each Mini PCIe slot supports one micro-SIM

4x RP-SMA antenna connector cutouts

In-system Expansion I/O

2x full size Mini PCI Express slots

1x Type A/B MXM slot on PCI Express x16 (MXM P1000, P3000, P5000)

1x USB 2.0 wafer connector

External I/O

2x USIM slots

4x M12 GbE with PoE ports

4x M12 GbE ports

2x RJ-45 GbE ports

6x DisplayPorts

1x DVI-I port

4x USB 3.0 Type A ports

1x Mic-in port

1x Line-out port

Four antenna cutouts reserved

Reset button

Power button

Specifications

• Miscellaneous

LEDs

1x diagnostics, 1x storage, 1x WDT, 3x user defined

Battery

Coin cell CR2032

Board Management

ADLINK SEMA 3.0:

- Watch Dog
- Hardware monitor
- Runtime statistics
- Failsafe dual BIOS

Power Supply

One 4-pin S-coded M12 connector
+12VDC nominal power input

Power Consumption

177W on AVA-5520/6820/32G/P5000 at

1. +12VDC in
2. CPU 100% loading
3. P5000 100% loading

• Mechanical

Dimension (WxDxH)

360mm x 225.1mm x 88.8mm

Weight

6.3 kg

Mounting

Wall mount

• Environmental

Operating Temperature

Convection cooled

-25°C to 70°C with P1000 MXM module

0°C to 55°C with P3000/P5000 MXM module

Storage Temperature

-40°C to +85°C

Humidity

EN 50125-1, compliance EN 60068-2-78: 2012 Edition 2.0, Clause 4.2 at 40°C

Vibration

1 m/s² @5 Hz – 150 Hz operating, according to EN61373

Shock

EN50155 standard, method EN61373: 2010, Category 1 Class A & Class B

Safety

EN 50153

UL 94V-0

Fire Protection

EN 45545-2:2013+A1:2015

EMC

EN 50121-3-2, EN50155

• Operating System

Windows 8, Windows 10

Ubuntu 16.04

Ordering Information

- **AVA-5520/7820/32G/P5000**
Fanless computer with Intel® Core™ i7-7820EQ and 32GB DDR4 with P5000 MXM module and two SATA bays (external cables and power adapter are excluded)
- **AVA-5520/6820/16G/P3000**
Fanless computer with Intel® Core™ i7-6820EQ and 16GB DDR4 with P3000 MXM module and two SATA bays (external cables and power adapter are excluded)

Optional Accessories

- **Factory-installed industrial grade SSD, single or dual 256GB options**
- **Starter cable kit for AVA-5520**
4x PoE M12(X) to RJ45 cable, 4x Ethernet M12 A(M) to RJ-45(F) cable, 1x PS/2 KB/MS Y cable and 1x M12(S) to DC power cable

Dimensions

(Units: mm)

