



EGX-MXM-RTX3000 (Preliminary)

Mobile PCI Express Module with NVIDIA® Quadro® Embedded RTX3000

Features

- NVIDIA® Quadro® RTX3000 embedded graphics
- Standard MXM 3.1 Type B form factor (82 x 105 mm)
- 2304 CUDA cores, 36 RT cores, and 288 Tensor cores
- 6.4 TFLOPS peak FP32 performance
- 6GB GDDR6 memory, 192-bit
- 336GB/s maximal memory bandwidth
- Support up to 4 DP 1.4b displays, 80W TGP
- 5-year availability



Introduction

The EGX-MXM-RTX3000 module features advanced NVIDIA® Turing™ GPU technology in MXM 3.1 Type B form factor. It's compact, slim and reliable design makes it suitable for mission critical environment. EGX-MXM-RTX3000 supports 4 DP1.4b displays offering a flexible and easy solution for medical and gaming applications.

Ordering Information

- **EGX-MXM-RTX3000**
 NVIDIA® Quadro® RTX3000 Embedded Graphics, MXM 3.1 type B, 82 x 105mm, PCIe x16 Gen3

Specifications

Model Name	EGX-MXM-RTX3000
Graphic Core	
GPU	Quadro® RTX3000
Memory	6GB GDDR6 memory, 192-bit, Bandwidth: 336 GB/s
GPGPU Computing	
CUDA Cores	2304 CUDA® cores, 6.4 TFLOPS Peak FP32 performance
Tensor Cores	288 Tensor Cores
Compute API	CUDA Toolkit 8.0 and above, CUDA Compute version 6.1 and above, OpenCL™ 1.2
Graphics API	DirectX® 12, OpenGL 4.6, Vulkan 1.0 API
Display	
Display Outputs	4x DisplayPort 1.4b digital video outputs 4K at 120Hz or 8K at 60Hz
Interface	MXM 3.1, PCI Express Gen3 x16 support
Mechanicals	
Dimensions	82 (W) x 105 (D) x 4.8 (H) mm
Form Factor	Standard MXM 3.1 Type B
Environmental	
Operating Temp.	Standard: 0°C to 55°C, ETT: TBC
Storage Temp.	-40°C to 85°C
Module Power Consumption	80W TGP
SW Support	
OS Support	Windows 10 & Linux Drivers, 64-bit