



MSBP2311AMC

23.8" Medical Display

- > IP65 in front & IPx1 whole unit
- > ALS (optional)
- > Calibration mode(optional)
- > 20 meter DVI/15 meter HDMI long cable solution

+ Spec

Panel	
LCD Size	23.8"
Display Type	FHD
Resolution	1920 x 1080
Luminance	230 Cd/m2
Contrast ratio	3000:1
Viewing angle	89/89 Deg. Horizontal & Vertical
Backlight	LED
Touch Type	Projective Capacitive
AG Protection Glass	Yes
DICOM compliant	Yes
I/O	
RS232	Optional
Input Interface	1 x VGA 1 x DVI 1 x HDMI 1 x Display Port
Mechanical & Environmental	
Power Type	DC-24V
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)
Storage Temperature	-20°C ~ 60°C (-4°F ~ 140°F)
Operating Humidity	10%~90% Relative Humidity, Non-condensing
Weight	7.4 Kgs
Construction	Plastic
Mounting Kit	Stand (Optional) VESA Mount kit (Optional) Wall Mount kit (Optional)
Vibration Test	With SSD/mSATA: 1.5Grms, IEC 60068-2-64, Random, 5 ~ 500Hz, 30min/axis
Shock Test	With SSD/mSATA: 10Grms, IEC 60068-2-27, Half Sine, 11ms
System Fan	Fanless
Dimension	573.77 x 387.77 x 63.5 mm
Certifications	
Certification Information	CE(EN60601-1,EN60601-1-10) FCC certified cTUVus certified

+ Ordering

RCC-MM-GMD23G-01R (G2MSBP2311AMC2120)
 MSBP2311AMC with AG Glass 230nits
 23.8" 16:9/AG Glass/Plastic Case/1920x1080/LED/230nits/3000contrast/
 VGA/DVI/HDMI/DP
 Delta 90W Adapter
 Without: Power Cord, DVI cablex1/VGA cablex1

RCC-MM-GMD23T-01R (G2MSBP2311AMC2121)
 MSBP2311AMC with AG PCAP 220nits
 23.8" 16:9/AG PCAP/Plastic Case/1920x1080/LED/220nits/3000contrast/
 VGA/DVI/HDMI/DP
 Delta 90W Adapter
 Without: Power Cord, DVI cablex1/VGA cablex1