

X505
3-Port RS-232 (5-Pin)

Features

- 3-Port Non-Isolation 5-wire RS-232



Introduction

The X-board series are for I-7188XA, I-7188XB, I-7188XC, I-7188XG, I-7188EG, I-7188EX and uPAC-7186EX Series (uPAC-7186EX, uPAC-7186PEX, uPAC-7186EG, uPAC-7186EX-FD, uPAC-7186EX-SM).


Above one μ PAC can plug only one X-board.

X505 is a 3-Port Non-Isolation 5-wire RS-232 X-board for I-7188XB, I-7188XG, I-7188EX, I-7188EG and uPAC-7186EX Series.

Specifications

COM Ports	
Ports	3 x 5-wire RS-232 (TxD, RxD, RTS, CTS, GND)
Baud Rate	115200 bps Max. 1200 ~ 115200 bps 10 k, 20 k, 50 k, 125 k, 250 kbps, 500 k, 800 k, 1M 125 k, 250 k, 500 k
FIFO Size	16 bytes
Power	
Consumption	0.7 W
Mechanical	
Dimensions (mm)	38 mm x 64 mm
Environmental	
Operating Temperature	-25 ~ +75 °C
Storage Temperature	-40 ~ +80 °C
Humidity	5 ~ 90 %, Non-condensing

Pin Assignments



Ordering Information

X505 CR	3-Port RS-232 (5-Pin) (RoHS)
----------------	------------------------------