


MODEL: SD-19RML




FEATURES



Size / Type
19" LED Backlight




Brightness
1000 (typ.)



Contrast
1000: 1 (typ.)



Max. Colors
16.7 M



Viewing Angle
-85~85(H); -80~80(V);



Resolution
1280 x 1024 @ 60Hz

SPECIFICATION

SYSTEM FEATURES	
Processor	Intel® Baytrail N2930 1.83GHz
System Memory	DDR3L 4G (up to 16 GB)
Storage	SSD 128GB (up to 1TB)
OS	Windows 7 / Windows 10 (optional)
INPUT / OUTPUT	
Back Side I/O (D38999/24WH53SN)	4 x USB 2.0, 1 x RS232, 1 x GbE LAN, 1 x RS422, 1 x VGA Output
Back Side I/O (D38999/26WD5PN)	1 x AC 110~240 V / 60Hz Input
Front Side I/O (optional)	2 x IP67 Type A USB 2.0 connectors
PANEL SPECIFICATION	
Size / Type	19" (LED Backlight, with sunlight readable)
Resolution	1280 x 1024
Brightness	1,000 nits (High Brightness)
Contrast Ratio	1000 : 1 (typ.)
Max. Colors	16.7M
Viewing Angle	- 85~ 85 (H); - 80~ 80 (V)
Touch Screen	5 - wire resistive touch
ENVIRONMENT TOLERANCE	
Operating Temperature	-20 deg. C to 60 deg. C
Storage Temperature	-30 deg. C to 70 deg. C
Humidity	10 to 95% (Non Condensing)
Shock	MIL-STD-810G Method 516.6
Vibration	MIL-STD-810G Method 514.6C-3
Humidity	MIL-STD-810G Method 507.5-7
High Temperature	MIL-STD-810G Method 501.5- II
Low Temperature	MIL-STD-810G Method 502.5
EMC (Compliance)	MIL-STD-461F, RE101, RE102, RS101, RS103, CE101, CE102, CS101, CS114, CS116
IP Level	Full IP67

FUNCTION KEY	
Power Button	1 x Power Button
Up / Down Arrow	Brightness Control Buttons
Other Buttons	Programmable buttons
LED Indicators	1 x Power On/Off, 1 x HDD Indicator

DIMENSIONS	
Dimensions	490 (W) x 420(H) x 72.5 (D) mm
Weight	11 KG

DRAWINGS

