## Model:MX30

## Features:

- Supports multiple label width & types.
- Drop & Fit label installation design.
- Water and dust resistant meeting IP54 standard.
- Versatile interfaces with both wire (RS232 and USB)
  & wireless (Bluetooth) connectivity.



Print Method		Direct Thermal
Resolution		203 dpi (8dots/mm)
Print Speed		Up to 4 IPS (101.6 mm/s)
Print Width		2.8" (72mm)
Print Length		30" (~762mm)
Processor		32 Bit RISC CPU
Memory Flash		128 MB Flash (60 MB for user storage)
SDRAM		32MB
Interfaces		RS232 + USB 2.0 port, mini-B type connector
		Bluetooth 2.1+EDR
Control Panel		4 dual color LEDs for Power, Battery, Communication, Error status indication.
		3 buttons for Power, Feed and BT functions
Power Adapter		Switching power supply
		I/P: 100/240V AC, 50/60Hz, DC 9V / 2.2A
Battery		Rechargeable DC 7.4 V Lithium-ion battery, 2500 mAh or higher capacitance
Environment	Operating Temperature	32°F to 122°F (0°C to 50°C)
	Storage Temperature	-4°F to 140°F (-20°C to 60°C)
Humidity	Operatioin	10-90%, non-condensing.
	Storage	10-90%, non-condensing.
IP Rating		Intrusion Protection, IP42 requirement for case design, IP54 for protective case
Drop Level		1.5 meter height
Dimention		6.71" x 3.11" x 4.48" (170.63mm x 79mm x 114.01mm)
Weight		1.45 lbs (660g), with battery



